Oracle 1z1-076ミシュレーション問題 & 1z1-076日本語資格取得



P.S. JpshikenがGoogle Driveで共有している無料かつ新しい1z1-076ダンプ：https://drive.google.com/open?id=1dn71IZlu2fb5z6QN5DIbJ-KflNrSW59t

Jpshikenは IT認定試験を受験した多くの人々を助けました。また、受験生からいろいろな良い評価を得ています。Jpshikenの1z1-076問題集の合格率が100%に達することも数え切れない受験生に証明された事実です。もし試験の準備をするために大変を感じているとしたら、ぜひJpshikenの1z1-076問題集を見逃さないでください。これは試験の準備をするために非常に効率的なツールですから。この問題集はあなたが少ない労力で最高の結果を取得することができます。

高品質の1z1-076の実際のテストと高い合格率のおかげで、当社はより速く、より速く開発され、世界で高い評価を得ています。教育の専門家は、試験問題と1z1-076研究急流の回答の設計と研究に精通しています。さらに、最新の1z1-076試験情報リソースをいつでも入手できます。学習ガイド資料には独自の利点があります。私たちの高い合格率は、この分野でトップの位置です。

>> Oracle 1z1-076ミシュレーション問題 <<

最短で確実に合格！ 1z1-076 試験問題

弊社のIT業で経験豊富な専門家たちが正確で、合理的なOracle 1z1-076認証問題集を作り上げました。 弊社の勉強の商品を選んで、多くの時間とエネルギーを節約こともできます。

Oracle Database 19c: Data Guard Administration 認定 1z1-076 試験問題 (Q54-Q59):

質問 # 54
Examine the Data Guard configuration:
What happens if you issue "switchover to sheep;" at the DGMGRL prompt?

- A. The switchover succeeds and Cats becomes the new failover target.
- B. The switchover succeeds and Fast-Start Failover is suspended.
- C. The switchover succeeds but Dogs needs to be reinstated.
- D. It results in an error indicating that a switchover is not allowed.
- E. The switchover succeeds and Dogs becomes the new failover target.

正解：E

解説：
When issuing a "switchover to sheep;" command in a Data Guard configuration, the primary database (Dogs) transitions to a standby role, and the target standby database (Sheep) becomes the new primary database. Fast-Start Failover (FSFO) remains enabled, but its target changes according to the new roles of the databases. Since Cats is also a physical standby database, it does not become the failover target by default unless it is specified in the broker configuration. After the switchover, the original primary (Dogs) becomes the new standby database and thus the new failover target for FSFO.
Reference:
Oracle Data Guard Broker documentation provides detailed procedures and explanations of switchover operations, including how FSFO targets are affected post-switchover. This behavior is consistent across different Oracle Database versions that support Data Guard and FSFO.

質問 # 55

Active Data Guard (ADG) databases are widely used to offload reporting or ad hoc query-only jobs from the primary database. Reporting workload profile is different from the primary database and often requires tuning.
Which tool is used to tune SQL workloads running on an ADG database?

- A. Automatic Workload Repository (AWR)
- B. Standby Statspack
- C. In-Memory Active Session History (ASH)
- D. Automatic Diagnostic Database Monitor (ADDM)
- E. SQL Tuning Advisor

正解：A

解説：
AWR collects, processes, and maintains performance statistics for problem detection and self-tuning purposes. In an Active Data Guard environment, where the physical standby database can be used for read-only workloads, AWR can be instrumental in identifying performance bottlenecks and areas for optimization. It provides detailed reports that include wait events, time model statistics, and active session history, making it an invaluable tool for tuning SQL queries and overall database performance in an ADG setup.

質問 # 56
Your Data Guard environment contains a four-instance RAC primary database whose SID is PROD and a RAC physical standby database whose std is PROD_SBY.
Examine the command executed on a node of the primary database cluster to create a service OLTPWORKLOAD that the applications will use to connect to the database when it is in the FRIMARYTclatabase role:
srvctl add service -db PROD -service oltpworkload -role PRIMARY -failovertype SESSION -failovermethod BASIC -failoverdelay 10 -failoverretry 150 The service is then started Consider this list of tasks:
1. On a node of the standby database cluster execute:
srvctl add service -db PROD_SBY -service oltpworkload -role PRIMARY -failovertype SESSION
-failovermethod BASIC -failoverdelay 10 -failoverretry 150
2. On the primary database, create the oltpworkload database service using the dbms_service.create_service procedure.
3. Configure tap for clients in the tnsnames.ora files.
4. Make sure clients use the OLTPWORKLOAD service to connect to the database instances.
5. On the standby database, create the oltpworkload database service using the dbms_service.create_servi;l procedure.
Identify the required steps to configure and use Transparent Application Failover (taf).

- A. 2,3,4
- B. 0
- C. 1,3,4
- D. 1
- E. 1.4
- F. 3,4

正解：E

解説：
To set up Transparent Application Failover (TAF) in a Data Guard environment with RAC, you would need to:
* On a node of the standby database cluster, execute the srvctl command to add the oltpworkload service for the PRIMARY role (1): This prepares the standby cluster to provide the oltpworkload service in case a failover occurs, and the standby becomes the primary database.
* Make sure clients use the OLTPWORKLOAD service to connect to the database instances (4):
This ensures that client connections are directed to the correct service, which is managed by TAF and can fail over in case of a primary database outage.References:
* Oracle Real Application Clusters Administration and Deployment Guide
* Oracle Data Guard Concepts and Administration Guide

質問 # 57
Your Data Guard environment contains a four-instance RAC primary database whose SID is PROD and a RAC physical standby database whose std is PROD_SBY.
Examine the command executed on a node of the primary database cluster to create a service OLTPWORKLOAD that the

applications will use to connect to the database when it is in the FRlMARYTclatabase role:
srvctl add service -db PROD -service oltpworkload -role PRIMARY -failovertype SESSION -failovermethod BASIC -failoverdelay 10 -failoverretry 150 The service is then started Consider this list of tasks:
1. On a node of the standby database cluster execute:
srvctl add service -db PROD_SBY -service oltpworkload -role PRIMARY -failovertype SESSION -failovermethod BASIC -failoverdelay 10 -failoverretry 150
2. On the primary database, create the oltpworkload database service using the dbms_service.create_service procedure.
3. Configure tap for clients in the tnsnames.ora files.
4. Make sure clients use the OLTPWORKLOAD service to connect to the database instances.
5. On the standby database, create the oltpworkload database service using the dbms_service.create_servi;l procedure.
Identify the required steps to configure and use Transparent Application Failover (taf).

- A. 2,3,4
- B. 0
- C. 1,3,4
- D. 1
- E. 1.4
- F. 3,4

正解：E

解説：
To set up Transparent Application Failover (TAF) in a Data Guard environment with RAC, you would need to:
On a node of the standby database cluster, execute the srvctl command to add the oltpworkload service for the PRIMARY role (1): This prepares the standby cluster to provide the oltpworkload service in case a failover occurs, and the standby becomes the primary database.
Make sure clients use the OLTPWORKLOAD service to connect to the database instances (4): This ensures that client connections are directed to the correct service, which is managed by TAF and can fail over in case of a primary database outage.
Reference:
Oracle Real Application Clusters Administration and Deployment Guide
Oracle Data Guard Concepts and Administration Guide

質問 # 58
You notice that the SQL apply lag on your logical standby database has increased but the redo transport lag has not.
Which four could be reasons for the increase in SQL apply lag?

- A. An increased number of bulk updates on the primary
- B. An undersized shared pool
- C. Many SQL apply operations do full table scans
- D. An increased number of bulk inserts on the primary
- E. The standby redo log files are undersized on the primary database
- F. An undersized undo tablespace on the logical standby

正解：A、B、C、F

解説：
The SQL apply lag on a logical standby database can be caused by several factors:
* A: An undersized undo tablespace can lead to delays in SQL apply operations as it may not be able to handle the volume of undo records generated by the SQL apply process.
* B: SQL apply operations that do full table scans can consume significant system resources, potentially leading to higher apply lag.
* C: An increased number of bulk updates on the primary database may generate a large volume of redo data, which can cause apply lag if the logical standby cannot apply the changes quickly enough.
* F: An undersized shared pool may affect the parsing and execution of SQL statements by SQL apply, which can contribute to the apply lag.
Option D is less likely to be a direct cause of SQL apply lag compared to bulk updates, as inserts generate new data rather than modifying existing data, which SQL apply can typically handle more efficiently.
Option E is incorrect because the size of the standby redo log files on the primary database impacts redo transport lag, not SQL apply lag.
References: Oracle Database High Availability Overview and Oracle Data Guard Concepts and Administration guide provide insights into the factors affecting SQL apply performance on logical standby databases.

質問 # 59
.....

クライアントが当社の1z1-076ガイド資料の習熟度を理解し、テストの準備を整えるために、テストプラクティスソフトウェアをクライアントに提供します。 1z1-076実践ガイドのテスト実践ソフトウェアは、実際のテスト問題に基づいており、そのインターフェースは使いやすいです。テスト練習ソフトウェアは、実際のテストを刺激し、複数の練習モデル、1z1-076トレーニング教材の練習の履歴記録、自己評価機能を高めるテストスキームを向上させます。

1z1-076日本語資格取得: https://www.jpshiken.com/1z1-076_shiken.html

1z1-076試験トレントのデータは前向きであり、ユーザーが最新の知識を習得するのに役立つホットトピックを把握できます、これにより多くの時間を節約でき、1z1-076試験問題の合格率は98％以上なので、1z1-076テストガイドで満足する可能性が高くなります、Oracle 1z1-076ミシュレーション問題 ただ20〜30時間を取って我々の試験材料をうまく把握するだけで十分でです、また、我々の提供する1z1-076有効練習問題は実際試験問題とほぼ同じです、一部の試験受験者は、有用な1z1-076の実際のテストを切望しているため、当社の製品は、効率的な練習資料が非常に不足しているお客様やその他のお客様に役立ちます、Oracle 1z1-076ミシュレーション問題購入後の一年間無料アップデート。

加納かのう城しろにもどると、赤あか兵衛ひょうえに用件ようけんの筋すじを云いいきかせ、すぐ京きょうにのぼらせた、まだ今日さえ不審の晴れない人のことに似た話ですね、1z1-076試験トレントのデータは前向きであり、ユーザーが最新の知識を習得するのに役立つホットトピックを把握できます。

1z1-076試験の準備方法｜実際的な1z1-076ミシュレーション問題試験｜最高のOracle Database 19c: Data Guard Administration日本語資格取得

これにより多くの時間を節約でき、1z1-076試験問題の合格率は98％以上なので、1z1-076テストガイドで満足する可能性が高くなります、ただ20〜30時間を取って我々の試験材料をうまく把握するだけで十分でです、また、我々の提供する1z1-076有効練習問題は実際試験問題とほぼ同じです。

一部の試験受験者は、有用な1z1-076の実際のテストを切望しているため、当社の製品は、効率的な練習資料が非常に不足しているお客様やその他のお客様に役立ちます。

- 1z1-076認証pdf資料 □ 1z1-076ウェブトレーニング □ 1z1-076模擬体験 □ ☀ www.passtest.jp □☀□の無料ダウンロード□ 1z1-076 □ページが開きます1z1-076勉強方法
- 認定テキストの超定番 1z1-076 試験対応 □ 《 1z1-076 》の試験問題は ➡ www.goshiken.com □□□で無料配信中1z1-076模擬体験
- 1z1-076ミシュレーション問題: Oracle Database 19c: Data Guard Administration豊かな問題を得る1z1-076日本語資格取得 □（ jp.fast2test.com ）サイトで【 1z1-076 】の最新問題が使える1z1-076認定資格試験問題集
- 1z1-076認定資格試験問題集 □ 1z1-076資格練習 □ 1z1-076的中率 □ サイト▶ www.goshiken.com◀で（ 1z1-076 ）問題集をダウンロード1z1-076模擬体験
- 1z1-076受験内容 □ 1z1-076認証pdf資料 □ 1z1-076入門知識 □ ➤ 1z1-076 □を無料でダウンロード➠ www.it-passports.com □で検索するだけ1z1-076ウェブトレーニング
- 1z1-076ミシュレーション問題: Oracle Database 19c: Data Guard Administration豊かな問題を得る1z1-076日本語資格取得 □ 今すぐ➽ www.goshiken.com □で（ 1z1-076 ）を検索し、無料でダウンロードしてください1z1-076対策学習
- 1z1-076認証pdf資料 □ 1z1-076資格講座 □ 1z1-076必殺問題集 □ “jp.fast2test.com”にて限定無料の✔ 1z1-076 □✔□問題集をダウンロードせよ1z1-076問題無料
- 1z1-076ミシュレーション問題: Oracle Database 19c: Data Guard Administration豊かな問題を得る1z1-076日本語資格取得 □ { www.goshiken.com }を入力して□ 1z1-076 □を検索し、無料でダウンロードしてください1z1-076入門知識
- 1z1-076必殺問題集 □ 1z1-076認証pdf資料 □ 1z1-076対策学習 □ ☀ www.passtest.jp □☀□に移動し、☀ 1z1-076 □☀□を検索して、無料でダウンロード可能な試験資料を探します1z1-076合格受験記
- 1z1-076試験の準備方法｜効果的な1z1-076ミシュレーション問題試験｜100％合格率のOracle Database 19c: Data Guard Administration日本語資格取得 □ ➽ www.goshiken.com □サイトにて最新□ 1z1-076 □問題集をダウンロード1z1-076日本語版参考資料
- 1z1-076認定資格試験問題集 □ 1z1-076認証pdf資料 □ 1z1-076模擬体験 □ □ www.goshiken.com □サイトで⇒ 1z1-076 ⇐の最新問題が使える1z1-076受験内容
- myportal.utt.edu.tt, myportal.utt.edu.tt, myportal.utt.edu.tt, myportal.utt.edu.tt, myportal.utt.edu.tt, myportal.utt.edu.tt, myportal.utt.edu.tt, myportal.utt.edu.tt, myportal.utt.edu.tt, myportal.utt.edu.tt, www.stes.tyc.edu.tw, myportal.utt.edu.tt,

ちなみに、Jpshiken 1z1-076の一部をクラウドストレージからダウンロードできます：https://drive.google.com/open?id=1dn71IZlu2fb5z6QN5DIbJ-KflNrSW59t