

Certification Cisco 300-430 Exam, 300-430 100% Correct Answers



DOWNLOAD the newest RealValidExam 300-430 PDF dumps from Cloud Storage for free: <https://drive.google.com/open?id=1jZRzuZAMG4T1HMnAbYnuQoGuf5IgaywX>

Combined with your specific situation and the characteristics of our 300-430 exam questions, our professional services will recommend the most suitable version of 300-430 study materials for you. We introduce a free trial version of the 300-430 learning guide because we want users to see our sincerity. 300-430 exam prep sincerely hopes that you can achieve your goals and realize your dreams.

Introduction to Cisco 300-430: Implementing Cisco Enterprise Wireless Networks Exam

It is a 90-minute test affiliated with the CCNP Service Provider and Cisco Accredited Professional-wireless networks Implementation certifications. Cisco 300-430: Implementing Cisco Enterprise Wireless Networks exam tests the candidate's knowledge of different aspects of wireless networks and their core concepts, from the service provider. Different types of **310-430 practice test** helps the students to prepare for the exam.

>> Certification Cisco 300-430 Exam <<

Cisco 300-430 100% Correct Answers | 300-430 Guide Torrent

If you want to pass your 300-430 exam, we believe that our learning engine will be your indispensable choices. More and more people have bought our 300-430 guide questions in the past years. These people who used our products have thought highly of our 300-430 Study Materials. If you decide to buy our products and take it seriously consideration, we can make sure that it will be very easy for you to simply pass your exam and get the 300-430 certification in a short time.

Cisco Implementing Cisco Enterprise Wireless Networks Sample Questions (Q138-Q143):

NEW QUESTION # 138

A FlexConnect remote office deployment is using five 2702i APs indoors and two 1532i APs outdoors. When a code upgrade is performed and FlexConnect Smart AP Image Upgrade is leveraged, but no FlexConnect Master AP has been configured, how many image transfers between the WLC and APs will occur?

- A. 0
- B. 1
- C. 2
- D. 3

Answer: A

NEW QUESTION # 139

A network administrator managing a Cisco Catalyst 9800-80 WLC must place all iOS connected devices to the guest SSID on VLAN 101. The rest of the clients must connect on VLAN 102 to distribute load across subnets. To achieve this configuration, the administrator configures a local policy on the WLC. Which two configurations are required? (Choose two.)

- A. Assign a policy map under global security policy settings.
- B. Add local profiling policy under global security policy settings
- **C. Create a service template**
- D. Allow HTTP and DHCP profiling under policy map.
- **E. Enable device classification on global wireless settings.**

Answer: C,E

NEW QUESTION # 140

An engineer must provide a graphical report with summary grouped data of the total number of wireless clients on the network. Which Cisco Prime Infrastructure report provides the required data?

- A. Posture Status Count
- **B. Mobility Client Summary**
- C. Client Traffic Stream Metrics
- D. Client Summary

Answer: B

Explanation:

https://www.cisco.com/c/en/us/td/docs/net_mgmt/prime/infrastructure/2-0/user/guide/prime_infra_ug/rep.html

NEW QUESTION # 141

After looking in the logs, an engineer notices that RRM keeps changing the channels for non-IEEE 802.11 interferers. After surveying the area, it has been decided that RRM should not change the channel. Which feature must be enabled to ignore non-802.11 interference?

- A. Avoid Cisco AP Load
- B. Avoid Foreign AP Interference
- **C. Avoid Persistent Non-WiFi Interference**
- D. Avoid Non-802.11 Noise

Answer: C

Explanation:

The feature that must be enabled to ignore non-802.11 interference is "Avoid Persistent Non-WiFi Interference." This setting allows the Radio Resource Management (RRM) to not react to non-802.11 noise and interference, which can be crucial in environments where such interference is common but does not significantly impact wireless performance. By enabling this feature, RRM will not change the channel in response to non-IEEE 802.11 interferers, thus maintaining a stable channel plan. References = (CCNP Enterprise Wireless Design ENWLS0 300-425 and Implementation ENWLSI 300-430 Official Cert Guide)

NEW QUESTION # 142

An engineer needs to configure an autonomous AP for 802.1X authentication. To achieve the highest security an authentication server is used for user authentication. During testing, the AP fails to pass the user authentication request to the authentication server. Which two details need to be configured on the AP to allow communication between the server and the AP? (Choose two.)

- **A. RADIUS IP address**
- **B. Username and password**
- C. PAC encryption key
- D. Group name
- E. Shared secret

Answer: A,B

• • • • •

300-430 100% Correct Answers: <https://www.realvalidexam.com/300-430-real-exam-dumps.html>

- BTW, DOWNLOAD part of RealValidExam 300-430 dumps from Cloud Storage: <https://drive.google.com/open?id=1jZRzuZAMG4T1HmNabYnuQoGuF5IgaywX>

BTW, DOWNLOAD part of RealValidExam 300-430 dumps from Cloud Storage: <https://drive.google.com/open?id=1jZRzuZAMG4T1HmNabYnuQoGuF5IgaywX>