

Reliable NCM-MCI Test Braindumps | Efficient Nutanix New NCM-MCI Exam Practice: Nutanix Certified Master - Multicloud Infrastructure v6.10



What's more, part of that PassCollection NCM-MCI dumps now are free: <https://drive.google.com/open?id=1MW3Aw011CoEqe7JpqrIZFtOhySw5Wcn>

Our NCM-MCI study guide provides free trial services, so that you can learn about some of our topics and how to open the software before purchasing. During the trial period of our NCM-MCI study materials, the PDF versions of the sample questions are available for free download, and both the pc version and the online version can be illustrated clearly. You can contact us at any time if you have any difficulties in the purchase or trial process of our NCM-MCI Exam Dumps.

Our company is responsible for our Nutanix Certified Master - Multicloud Infrastructure v6.10 exam cram. Every product we have sold to customer will enjoy considerate after-sales service. If you have problems about our NCM-MCI test guide such as installation, operation and so on, we will quickly reply to you after our online workers have received your emails. We are not afraid of troubles. We warmly welcome to your questions and suggestions. Now that you have spent money on our NCM-MCI Exam Questions, we have the obligation to ensure your comfortable learning. We do not have hot lines. So you are advised to send your emails to our email address. In case you send it to others' email inbox, please check the address carefully before. The after-sales service of our NCM-MCI exam questions can stand the test of practice. Once you trust our products, you also can enjoy such good service.

>> **Reliable NCM-MCI Test Braindumps** <<

New NCM-MCI Exam Practice & New NCM-MCI Exam Cram

The client can try out and download our NCM-MCI training materials freely before their purchase so as to have an understanding of our product and then decide whether to buy them or not. The website pages of our product provide the details of our NCM-MCI learning questions. You can see the demos which are part of the all titles selected from the test bank and the forms of the questions and answers and know the form of our software on the website pages of our study materials.

Nutanix Certified Master - Multicloud Infrastructure v6.10 Sample Questions

(Q17-Q22):

NEW QUESTION # 17

Task 9

Part1

An administrator logs into Prism Element and sees an alert stating the following:

Cluster services down on Controller VM (35.197.75.196)

Correct this issue in the least disruptive manner.

Part2

In a separate request, the security team has noticed a newly created cluster is reporting:

CVM [35.197.75.196] is using the default password.

They have provided some new security requirements for cluster level security.

Security requirements:

Update the default password for the root user on the node to match the admin user password: Note: 192.168.x.x is not available.

To access a node use the Host IP (172.30.0.x) from a CVM or the supplied external IP address.

Update the default password for the nutanix user on the CVM to match the admin user password.

Resolve the alert that is being reported.

Output the cluster-wide configuration of the SCMA policy to Desktop\Files\output.txt before changes are made.

Enable the Advance intrusion Detection Environment (AIDE) to run on a weekly basis for the cluster.

Enable high-strength password policies for the cluster.

Ensure CVMs require SSH keys for login instead of passwords. (SSH keys are located in the Desktop\Files\SSH folder).

Ensure the clusters meets these requirements. Do not reboot any cluster components.

Answer:

Explanation:

See the Explanation for step by step solution

Explanation:

To correct the issue of cluster services down on Controller VM (35.197.75.196) in the least disruptive manner, you need to do the following steps:

Log in to Prism Element using the admin user credentials.

Go to the Alerts page and click on the alert to see more details.

You will see which cluster services are down on the Controller VM. For example, it could be cassandra, curator, stargate, etc.

To start the cluster services, you need to SSH to the Controller VM using the nutanix user credentials. You can use any SSH client such as PuTTY or Windows PowerShell to connect to the Controller VM. You will need the IP address and the password of the nutanix user, which you can find in Desktop\Files\SSH\nutanix.txt.

Once you are logged in to the Controller VM, run the command:

```
cluster status | grep -v UP
```

This will show you which services are down on the Controller VM.

To start the cluster services, run the command:

```
cluster start
```

This will start all the cluster services on the Controller VM.

To verify that the cluster services are running, run the command:

```
cluster status | grep -v UP
```

This should show no output, indicating that all services are up.

To clear the alert, go back to Prism Element and click on Resolve in the Alerts page.

To meet the security requirements for cluster level security, you need to do the following steps:

To update the default password for the root user on the node to match the admin user password, you need to SSH to the node using the root user credentials. You can use any SSH client such as PuTTY or Windows PowerShell to connect to the node. You will need the IP address and the password of the root user, which you can find in Desktop\Files\SSH\root.txt.

Once you are logged in to the node, run the command:

```
passwd
```

This will prompt you to enter a new password for the root user. Enter the same password as the admin user, which you can find in Desktop\Files\SSH\admin.txt.

To update the default password for the nutanix user on the CVM to match the admin user password, you need to SSH to the CVM using the nutanix user credentials. You can use any SSH client such as PuTTY or Windows PowerShell to connect to the CVM.

You will need the IP address and the password of the nutanix user, which you can find in Desktop\Files\SSH\nutanix.txt.

Once you are logged in to the CVM, run the command:

```
passwd
```

This will prompt you to enter a new password for the nutanix user. Enter the same password as the admin user, which you can find in Desktop\Files\SSH\admin.txt.

To resolve the alert that is being reported, go back to Prism Element and click on Resolve in the Alerts page.

To output the cluster-wide configuration of SCMA policy to Desktop\Files\output.txt before changes are made, you need to log in to Prism Element using the admin user credentials.

Go to Security > SCMA Policy and click on View Policy Details. This will show you the current settings of SCMA policy for each entity type.

Copy and paste these settings into a new text file named Desktop\Files\output.txt.

To enable AIDE (Advanced Intrusion Detection Environment) to run on a weekly basis for the cluster, you need to log in to Prism Element using the admin user credentials.

Go to Security > AIDE Configuration and click on Enable AIDE. This will enable AIDE to monitor file system changes on all CVMs and nodes in the cluster.

Select Weekly as the frequency of AIDE scans and click Save.

To enable high-strength password policies for the cluster, you need to log in to Prism Element using the admin user credentials.

Go to Security > Password Policy and click on Edit Policy. This will allow you to modify the password policy settings for each entity type.

For each entity type (Admin User, Console User, CVM User, and Host User), select High Strength as the password policy level and click Save.

To ensure CVMs require SSH keys for login instead of passwords, you need to log in to Prism Element using the admin user credentials.

Go to Security > Cluster Lockdown and click on Configure Lockdown. This will allow you to manage SSH access settings for the cluster.

Uncheck Enable Remote Login with Password. This will disable password-based SSH access to the cluster.

Click New Public Key and enter a name for the key and paste the public key value from Desktop\Files\SSH\id_rsa.pub. This will add a public key for key-based SSH access to the cluster.

Click Save and Apply Lockdown. This will apply the changes and ensure CVMs require SSH keys for login instead of passwords.

Part1

Enter CVM ssh and execute:

```
cluster status | grep -v UP
```

```
cluster start
```

If there are issues starting some services, check the following:

Check if the node is in maintenance mode by running the `ncli host ls` command on the CVM. Verify if the parameter Under Maintenance Mode is set to False for the node where the services are down. If the parameter Under Maintenance Mode is set to True, remove the node from maintenance mode by running the following command:

```
* nutanix@cvm$ ncli host edit id=<host id> enable-maintenance-mode=false
```

 You can determine the host ID by using `ncli host ls`.

See the troubleshooting topics related to failed cluster services in the Advanced Administration Guide available from the Nutanix Portal's Software Documentation page. (Use the filters to search for the guide for your AOS version). These topics have information about common and AOS-specific logs, such as Stargate, Cassandra, and other modules.

* Check for any latest FATALs for the service that is down. The following command prints all the FATALs for a CVM. Run this command on all CVMs.

```
nutanix@cvm$ for i in `svnrips`; do echo "CVM: $i"; ssh $i "ls -ltr /home/nutanix/data/logs/*.FATAL"; done
```

 NCC Health Check:

```
cluster_services_down_check (nutanix.com) Part2
```

 Update the default password for the root user on the node to match the admin

```
user password echo -e "CHANGING ALL AHV HOST ROOT PASSWORDS.\nPlease input new password: "; read -rs
```

```
password1; echo "Confirm new password: "; read -rs password2; if [ "$password1" = "$password2" ]; then for host in $(hostips);
```

```
do echo Host $host; echo $password1 | ssh root@$host "passwd --stdin root"; done; else echo "The passwords do not match"; fi
```

```
Update the default password for the nutanix user on the CVM sudo passwd nutanix
```

 Output the cluster-wide configuration of the

```
SCMA policy ncli cluster get-hypervisor-security-config
```

 Output Example:

```
nutanix@NTNX-372a19a3-A-CVM:10.35.150.184:~$ ncli cluster get-hypervisor-security-config
```

 Enable Aide : false Enable Core

```
: false Enable High Strength P... : false Enable Banner : false Schedule : DAILY Enable iTLB Multihit M... : false
```

 Enable the

```
Advance intrusion Detection Environment (AIDE) to run on a weekly basis for the cluster.
```

```
ncli cluster edit-hypervisor-security-params enable-aide=true
```

```
ncli cluster edit-hypervisor-security-params schedule=weekly
```

```
Enable high-strength password policies for the cluster.
```

```
ncli cluster edit-hypervisor-security-params enable-high-strength-password=true
```

 Ensure CVMs require SSH keys for login instead of passwords

```
https://portal.nutanix.com/page/documents/kbs/details?targetId=kA060000008gb3CAA
```

```
□
```

NEW QUESTION # 18

Task 7

An administrator has environment that will soon be upgraded to 6.5. In the meantime, they need to implement log and apply a

security policy named Staging_Production, such that not VM in the Staging Environment can communicate with any VM in the production Environment, Configure the environment to satisfy this requirement.

Note: All other configurations not indicated must be left at their default values.

Answer:

Explanation:

See the Explanation for step by step solution

Explanation:

To configure the environment to satisfy the requirement of implementing a security policy named Staging_Production, such that no VM in the Staging Environment can communicate with any VM in the production Environment, you need to do the following steps: Log in to Prism Central and go to Network > Security Policies > Create Security Policy. Enter Staging_Production as the name of the security policy and select Cluster A as the cluster.

In the Scope section, select VMs as the entity type and add the VMs that belong to the Staging Environment and the Production Environment as the entities. You can use tags or categories to filter the VMs based on their environment.

In the Rules section, create a new rule with the following settings:

Direction: Bidirectional

Protocol: Any

Source: Staging Environment

Destination: Production Environment

Action: Deny

Save the security policy and apply it to the cluster.

This will create a security policy that will block any traffic between the VMs in the Staging Environment and the VMs in the Production Environment. You can verify that the security policy is working by trying to ping or access any VM in the Production Environment from any VM in the Staging Environment, or vice versa. You should not be able to do so.

□

NEW QUESTION # 19

Task 5

An administrator has been informed that a new workload requires a logically segmented network to meet security requirements.

Network configuration:

VLAN: 667

Network: 192.168.0.0

Subnet Mask: 255.255.255.0

DNS server: 34.82.231.220

Default Gateway: 192.168.0.1

Domain: cyberdyne.net

IP Pool: 192.168.9.100-200

DHCP Server IP: 192.168.0.2

Configure the cluster to meet the requirements for the new workload if new objects are required, start the name with 667.

Answer:

Explanation:

See the Explanation for step by step solution

Explanation:

To configure the cluster to meet the requirements for the new workload, you need to do the following steps:

Create a new VLAN with ID 667 on the cluster. You can do this by logging in to Prism Element and going to Network Configuration > VLANs > Create VLAN. Enter 667 as the VLAN ID and a name for the VLAN, such as 667_VLAN.

Create a new network segment with the network details provided. You can do this by logging in to Prism Central and going to Network > Network Segments > Create Network Segment. Enter a name for the network segment, such as

667_Network_Segment, and select 667_VLAN as the VLAN. Enter 192.168.0.0 as the Network Address and 255.255.255.0 as the Subnet Mask. Enter 192.168.0.1 as the Default Gateway and 34.82.231.220 as the DNS Server. Enter cyberdyne.net as the Domain Name.

Create a new IP pool with the IP range provided. You can do this by logging in to Prism Central and going to Network > IP Pools > Create IP Pool. Enter a name for the IP pool, such as 667_IP_Pool, and select 667_Network_Segment as the Network Segment. Enter 192.168.9.100 as the Starting IP Address and 192.168.9.200 as the Ending IP Address.

Configure the DHCP server with the IP address provided. You can do this by logging in to Prism Central and going to Network > DHCP Servers > Create DHCP Server. Enter a name for the DHCP server, such as 667_DHCP_Server, and select 667_Network_Segment as the Network Segment. Enter 192.168.0.2 as the IP Address and select 667_IP_Pool as the IP Pool.

□

NEW QUESTION # 20

Topic 1, Performance Based Questions

Environment

You have been provisioned a dedicated environment for your assessment which includes the following:

Workstation

* windows Server 2019

* All software/tools/etc to perform the required tasks

* Nutanix Documentation and whitepapers can be found in desktop\files\Documentation

* Note that the workstation is the system you are currently logged into Nutanix Cluster

* There are three clusters provided. The connection information for the relevant cluster will be displayed to the high of the question

Please make sure you are working on the correct cluster for each item Please ignore any licensing violations

* Cluster A is a 3-node cluster with Prism Central 2022.6 where most questions will be performed

* Cluster B is a one-node cluster and has one syslog item and one security item to perform

* Cluster D is a one-node cluster with Prism Central 5.17 and has a security policy item to perform Important Notes

* If the text is too small and hard to read, or you cannot see an of the GUI. you can increase/decrease the zoom of the browser with CTRL + , and CTRL + (the plus and minus keys) You will be given 3 hours to complete the scenarios for Nutanix NCMCI Once you click the start button below, you will be provided with:

- A Windows desktop A browser page with the scenarios and credentials (Desktop\instructions) Notes for this exam delivery:

The browser can be scaled to Improve visibility and fit all the content on the screen.

- Copy and paste hot-keys will not work Use your mouse for copy and paste.

- The Notes and Feedback tabs for each scenario are to leave notes for yourself or feedback for

- Make sure you are performing tasks on the correct components.

- Changing security or network settings on the wrong component may result in a falling grade.

- Do not change credentials on an component unless you are instructed to.

- All necessary documentation is contained in the Desktop\Files\Documentation directory Task 1 An administrator has been asked to configure a storage for a distributed application which uses large data sets across multiple worker VMs.

The worker VMs must run on every node. Data resilience is provided at the application level and low cost per GB is a Key Requirement.

Configure the storage on the cluster to meet these requirements. Any new object created should include the phrase Distributed_App in the name.

Answer:

Explanation:

See the Explanation for step by step solution

Explanation:

To configure the storage on the cluster for the distributed application, you can follow these steps:

Log in to Prism Element of cluster A using the credentials provided.

Go to Storage > Storage Pools and click on Create Storage Pool.

Enter a name for the new storage pool, such as Distributed_App_Storage_Pool, and select the disks to include in the pool. You can choose any combination of SSDs and HDDs, but for low cost per GB, you may prefer to use more HDDs than SSDs.

Click Save to create the storage pool.

Go to Storage > Containers and click on Create Container.

Enter a name for the new container, such as Distributed_App_Container, and select the storage pool that you just created, Distributed_App_Storage_Pool, as the source.

Under Advanced Settings, enable Erasure Coding and Compression to reduce the storage footprint of the data. You can also disable Replication Factor since data resilience is provided at the application level. These settings will help you achieve low cost per GB for the container.

Click Save to create the container.

Go to Storage > Datastores and click on Create Datastore.

Enter a name for the new datastore, such as Distributed_App_Datastore, and select NFS as the datastore type. Select the container that you just created, Distributed_App_Container, as the source.

Click Save to create the datastore.

The datastore will be automatically mounted on all nodes in the cluster. You can verify this by going to Storage > Datastores and clicking on Distributed_App_Datastore. You should see all nodes listed under Hosts.

You can now create or migrate your worker VMs to this datastore and run them on any node in the cluster. The datastore will provide low cost per GB and high performance for your distributed application.

NEW QUESTION # 21

Task 3

An administrator needs to assess performance gains provided by AHV Turbo at the guest level. To perform the test the administrator created a Windows 10 VM named Turbo with the following configuration.

1 vCPU

8 GB RAM

SATA Controller

40 GB vDisk

The stress test application is multi-threaded capable, but the performance is not as expected with AHV Turbo enabled. Configure the VM to better leverage AHV Turbo.

Note: Do not power on the VM. Configure or prepare the VM for configuration as best you can without powering it on.

Answer:

Explanation:

See the Explanation for step by step solution

Explanation:

To configure the VM to better leverage AHV Turbo, you can follow these steps:

Log in to Prism Element of cluster A using the credentials provided.

Go to VM > Table and select the VM named Turbo.

Click on Update and go to Hardware tab.

Increase the number of vCPUs to match the number of multiqueues that you want to enable. For example, if you want to enable 8 multiqueues, set the vCPUs to 8. This will improve the performance of multi-threaded workloads by allowing them to use multiple processors.

Change the SCSI Controller type from SATA to VirtIO. This will enable the use of VirtIO drivers, which are required for AHV Turbo.

Click Save to apply the changes.

Power off the VM if it is running and mount the Nutanix VirtIO ISO image as a CD-ROM device. You can download the ISO image from Nutanix Portal.

Power on the VM and install the latest Nutanix VirtIO drivers for Windows 10. You can follow the instructions from Nutanix Support Portal.

After installing the drivers, power off the VM and unmount the Nutanix VirtIO ISO image.

Power on the VM and log in to Windows 10.

Open a command prompt as administrator and run the following command to enable multiqueue for the VirtIO NIC:

```
ethtool -L eth0 combined 8
```

Replace eth0 with the name of your network interface and 8 with the number of multiqueues that you want to enable. You can use `ipconfig /all` to find out your network interface name.

Restart the VM for the changes to take effect.

You have now configured the VM to better leverage AHV Turbo. You can run your stress test application again and observe the performance gains.

<https://portal.nutanix.com/page/documents/kbs/details?targetId=kA00e000000LKPdCAO> change vCPU to 2/4 ?

Change SATA Controller to SCSI:

```
acli vm.get Turbo
```

Output Example:

```
Turbo {
  config {
    agent_vm: False
    allow_live_migrate: True
    boot {
      boot_device_order: "kCdrom"
      boot_device_order: "kDisk"
      boot_device_order: "kNetwork"
    }
    uefi_boot: False
  }
  cpu_passthrough: False
  disable_branding: False
  disk_list {
    addr {
      bus: "ide"
```

```

index: 0
}
cdrom: True
device_uuid: "994b7840-dc7b-463e-a9bb-1950d7138671"
empty: True
}
disk_list {
addr {
bus: "sata"
index: 0
}
}
container_id: 4
container_uuid: "49b3e1a4-4201-4a3a-8abc-447c663a2a3e"
device_uuid: "622550e4-fb91-49dd-8fc7-9e90e89a7b0e"
naa_id: "naa.6506b8dcda1de6e9ce911de7d3a22111"
storage_vdisk_uuid: "7e98a626-4cb3-47df-a1e2-8627cf90eae6"
vmdisk_size: 10737418240
vmdisk_uuid: "17e0413b-9326-4572-942f-68101f2bc716"
}
flash_mode: False
hwclock_timezone: "UTC"
machine_type: "pc"
memory_mb: 2048
name: "Turbo"
nic_list {
connected: True
mac_addr: "50:6b:8d:b2:a5:e4"
network_name: "network"
network_type: "kNativeNetwork"
network_uuid: "86a0d7ca-acfd-48db-b15c-5d654fb39096"
type: "kNormalNic"
uuid: "b9e3e127-966c-43f3-b33c-13608154c8bf"
vlan_mode: "kAccess"
}
num_cores_per_vcpu: 2
num_threads_per_core: 1
num_vcpus: 2
num_vnuma_nodes: 0
vga_console: True
vm_type: "kGuestVM"
}
is_rfl_vm: False
logical_timestamp: 2
state: "Off"
uuid: "9670901f-8c5b-4586-a699-41f0c9ab26c3"
}
acli vm.disk_create Turbo clone_from_vmdisk=17e0413b-9326-4572-942f-68101f2bc716 bus=scsi remove the old disk acli
vm.disk_delete 17e0413b-9326-4572-942f-68101f2bc716 disk_addr=sata.0

```

NEW QUESTION # 22

.....

We are famous for our company made these NCM-MCI exam questions with accountability. We understand you can have more chances getting higher salary or acceptance instead of preparing for the NCM-MCI exam. Our NCM-MCI practice materials are made by our responsible company which means you can gain many other benefits as well. We offer free demos of our NCM-MCI learning guide for your reference, and send you the new updates if our experts make them freely.

New NCM-MCI Exam Practice: https://www.passcollection.com/NCM-MCI_real-exams.html

If you don't receive the NCM-MCI learning materials, please contact us, and we will solve it for you, That's why so many people

