

Cisco 350-901최신업데이트시험덤프 & 350-901시험덤프 프자료



BONUS!!! KoreaDumps 350-901 시험 문제집 전체 버전을 무료로 다운로드하세요: <https://drive.google.com/open?id=1rOTKZRSeLz7R5a0ZKJF5dFo8G5CV-UR3>

Cisco 350-901인증시험은 현재IT업계에서 아주 인기 있는 시험입니다.많은 IT인사들이 관련 자격증을 취득하려고 노력하고 있습니다.Cisco 350-901인증시험에 대한 열기는 식지 않습니다.Cisco 350-901자격증은 여러분의 사회생활에 많은 도움이 될 것이며 연봉상승 등 생활보장에 업그레이드 될 것입니다.

Cisco 350-901 (Developing Applications using Cisco Core Platforms and APIs (DEVCOR)) 자격증 시험은 Cisco 기술을 사용하여 응용 프로그램 개발에 대한 전문 지식을 개발하고자하는 IT 전문가들에게 유용한 자격증입니다. 광범위한 주제를 다루며, 후보자는 Cisco 플랫폼, 프로그래밍 언어 및 자동화 도구에 대한 견고한 이해력이 필요합니다. 이 자격증을 취득하면 응용 프로그램 개발 분야에서 경력을 발전시키고 잠재적인 고용주에게 자신의 기술과 지식을 증명하고자하는 IT 전문가들에게 이점이 있을 수 있습니다.

>> Cisco 350-901최신 업데이트 시험덤프 <<

350-901시험덤프자료 - 350-901최신 업데이트 인증시험자료

Cisco인증 350-901시험을 패스하여 자격증을 취득하는게 꿈이라구요? KoreaDumps에서 고객님의Cisco인증 350-901 시험패스꿈을 이루어지게 지켜드립니다. KoreaDumps의 Cisco인증 350-901덤프는 가장 최신시험에 대비하여 만들어진 공부자료로서 시험패스는 한방에 끝내줍니다.

최신 Cisco Certified DevNet Professional 350-901 무료샘플문제 (Q367-Q372):

질문 # 367

Refer to the exhibit.

Data Parameters			HTTP request URL
Parameter	Required	Type	Description
name	True	string	A string that is the name of the network object.
description	False	string	A string containing the description information Field level constraints: length must be between 0 and 200 (inclusive). (Note: Additional constraints might exist)
subType	True	string	An enum value that specifies the network object type HOST - A host type. NETWORK - A network type. FQDN - A FQDN type. RANGE - A range type. Field level constraints: cannot be null. (Note: Additional constraints might exist)
value	True	string	A string that defines the address content for the object. For HOST objects, this is a single IPv4 or IPv6 address without netmask or prefix. For NETWORK objects, this is an IPv4 or IPv6 network address with netmask (in CIDR notation) or prefix. For FQDN objects, this is a Fully qualified domain name. For RANGE objects, this is IPv4 or IPv6 addresses separated by '-' Field level constraints: cannot be null, must match pattern ^((?!:).)*\$. (Note: Additional constraints might exist)
isSystemDefined	False	boolean	A Boolean value, TRUE or FALSE(the default). The TRUE value indicates that this Network object is a system defined object
dnsResolution	False	string	DNS Resolution type can be IPV4_ONLY, IPV6_ONLY or IPV4_AND_IPV6
type	True	string	A UTF8 string, all letters lower-case, that represents the class-type. This corresponds to the class name.

Refer to the exhibit. Drag and drop the code snippets from the bottom onto the blanks in the code to create a function to add new network objects to their Firepower Device Management instance. Not all options are used.

```
import requests
def new_network_object(TOKEN):
    url = f'https://{HOST}/api/fdm/latest/object/'
    headers = {
        'Content-Type': 'application/json',
        'Accept': 'application/json',
        'Authorization': f'Bearer {TOKEN}'
    }
    body = {
        'subtype': ' ',
        'value': '10.10.10.0/24',
        'type': ' '
    }
    response = requests.post(url, verify=False, headers=headers, json=body)
```

networks	networkobject	network_type
NETWORK	networktype	device

정답:

설명:

```
import requests
def new_network_object(TOKEN):
    url = f'https://{HOST}/api/fdm/latest/object/'
    headers = {
        'Content-type': 'application/json',
        'Accept': 'application/json',
        'Authorization': f'Bearer {TOKEN}'
    }
    body = {
        'subtype': ' ',
        'value': '10.10.10.0/24',
        'type': ' '
    }
    response = requests.post(url, verify=False, headers=headers, json=body)
```

networks	networkobject	network_type
NETWORK	networktype	device

질문 # 368

Refer to the exhibit.

```

headers = (
try:
    response = requests.get("https://sandboxdnac.cisco.com/dna/intent/api/v1/wireless/profile",
        headers=headers, verify=False)
except requests.exceptions.RequestException as cerror:
    print("Error processing request", cerror)
    sys.exit(1)

```

Which code snippet is required in the headers to successfully authorize wireless information from Cisco DNA Center?

- A. headers = {'Content-type': 'application/json'}
- B. headers = {'Authorization': 'Bearer ASDNFALKJER23412RKDALSNKF'}
- C. headers = {'Authorization': 'Basic YWRtaW46R3JhcGV2aW5IMQ=='}
- D. headers = {'X-auth-token': 'fa8426a0-8eaf-4d22-8e13-7c1b16a9370c'}

정답: D

질문 # 369

An engineer must access multiple bots that are running in an internal infrastructure. A different HTTPS URL is required for each bot. The infrastructure has just one public IP address and a Linux server with Apache installed. Drag and drop the actions from the left into the order of steps on the right to enable access to the bots inside. Not all options are used.

Configure "Let's Encrypt" on the bot servers.	step 1
Enable a forward proxy in Apache.	step 2
Configure Apache virtual hosts.	step 3
Enable a reverse proxy in Apache.	
Configure an Apache .htaccess file.	
Configure "Let's Encrypt" on the Apache server.	

정답:

설명:

Configure "Let's Encrypt" on the bot servers.	Configure Apache virtual hosts. 1
Enable a forward proxy in Apache.	Configure "Let's Encrypt" on the Apache server.
Configure Apache virtual hosts.	Enable a reverse proxy in Apache.
Enable a reverse proxy in Apache.	
Configure an Apache .htaccess file.	
Configure "Let's Encrypt" on the Apache server.	

질문 # 370

Refer to the exhibit. A Python script must list network clients in the Cisco Meraki API that have used a network with an ID of 2. The number of client entries per returned page is restricted to 1,000 according to the API specification. Network 2 has 2,500 clients.

```

1  import requests
2  url = "https://api.meraki.com/api/v0/networks/2/clients"
3  payload = None
4  headers = {
5      "Content-Type": "application/json",
6      "Accept": "application/json",
7      "X-Cisco-Meraki-API-Key": "1b87b584fb5411eaadc1024ac120002"
8  }
9  response = requests.request('GET', url, headers=headers, data = payload)
10 print (response.text.encode('utf8'))
11

```

What must be added where the code is missing to print the content of each response?

• A.

```

url = "https://api.meraki.com/api/v0/networks/2/clients?startingAfter=1000"
response = requests.get(url)
print (response.text)

```

• B.

```

if response.links.get('next'):
    url = response.links['next'] ['url']
    response = requests.get(url)
    print (response.text)

```

• C.

```

url = "https://api.meraki.com/api/v0/networks/2/clients?perPage=1500"
response = requests.get (url)
print (response.text)

```

• D.

```

if response.links.get('next'):
    url = links['url']
    response = requests.get (url)
    print (response.text)

```

정답: B

질문 # 371

Drag and Drop Question

Refer to the exhibit. Drag and drop the code snippets from the left onto the item numbers on the right that match the missing sections in the cURL exhibit to complete the cURL request to FirePower Device Manager API to create objects. Not all code snippets are used.

Description

The addNetworkObject operation handles configuration related to [NetworkObject](#) model.

This API call is not allowed on the standby unit in an HA pair.

HTTP request

URL

```
POST /api/fdm/v4/object/networks
```

Data Parameters

Parameter	Required	Type	Description
name	True	string	A string that is the name of the network object.
description	False	string	A string containing the description information. Field level constraints: length must be between 0 and 200 (inclusive). (Note: Additional constraints might exist)
subType	True	string	An enum value that specifies the network object type. HOST - A host type. NETWORK - A network type. FQDN - A FQDN type. RANGE - A range type. Field level constraints: cannot be null. (Note: Additional constraints might exist)
value	True	string	A string that defines the address content for the object. For HOST objects, this is a single IPv4 or IPv6 address without netmask or prefix. For NETWORK objects, this is an IPv4 or IPv6 network address with netmask (in CIDR notation) or prefix. For FQDN objects, this is a Fully qualified domain name. For RANGE objects, this is IPv4 or IPv6 addresses separated by '-'. Field level constraints: cannot be null, must match pattern ^((?!:).)*\$ (Note: Additional constraints might exist)
isSystemDefined	False	boolean	A Boolean value. TRUE or FALSE(the default). The TRUE value indicated that this Network object is a system defined object.
dnsResolution	False	string	DNS Resolution type can be IPV4_ONLY, IPV6_ONLY or IPV4_AND_IPV6.
type	True	string	A UTF8 string, all letters lower-case, that represents the class-type. This corresponds to the class name.

```
curl -X <item 1> -H "Authorization: Bearer exwsxads-sadads0as0d0-1w-1-1w-1w" --header 'Content-Type: application/json' --header 'Accept: application/json' -d '{
  "name": "171.168.1.z",
  "value": "<item 2>",
  "subType": "<item 3>",
  "type": "<item 4>"
}' 'https://ast0072-pod.cisco.com:33333/api/fdm/v4/object/<item 5>
```

Answer Area

HOST	<item 1>
POST	<item 2>
NETWORK	<item 3>
networks	<item 4>
networkobject	<item 5>
171.168.1.0/24	
False	
isSystemDefined	

정답:

설명:

Answer Area

HOST	POST
	171.168.1.0/24
	NETWORK
	networkobject
	networks
False	
isSystemDefined	

질문 # 372

.....

KoreaDumps 에서 제공해드리는 Cisco 350-901덤프는 아주 우수한 IT인증덤프자료 사이트입니다. IT업계엘리트한

BONUS!!! KoreaDumps 350-901 시험 문제집 전체 버전을 무료로 다운로드하세요: <https://drive.google.com/open?id=1rOTKZRSeLz7R5a0ZKJF5dFo8G5CV-UR3>