

HPE0-S59최신인증시험덤프데모 & HPE0-S59최고덤프자료



그리고 DumpTOP HPE0-S59 시험 문제집의 전체 버전을 클라우드 저장소에서 다운로드할 수 있습니다:
https://drive.google.com/open?id=10HKFA8-kO0JGs1bW4SvcdDpLvX-JI3_x

DumpTOP는 고객님의 IT자격증취득의 작은 소원을 이루어지게 도와드리는 IT인증시험덤프를 제공해드리는 전문적인 사이트입니다. DumpTOP 표 HP인증HPE0-S59시험덤프가 있으면 인증시험걱정을 버리셔도 됩니다. DumpTOP 표 HP인증HPE0-S59덤프는 시험출제 예상문제를 정리해둔 실제시험문제에 가장 가까운 시험준비공부자료로서 공을 들이지않고도 시험패스가 가능합니다.

지금 같은 정보시대에, 많은 IT업체 등 사이트에HP HPE0-S59인증관련 자료들이 제공되고 있습니다, 하지만 이런 사이트들도 정확하고 최신 시험자료 확보는 아주 어렵습니다. 그들의HP HPE0-S59자료들은 아주 기본적인 것들뿐입니다. 전면적이지 못하여 응시자들의 관심을 끌지 못합니다.

>> HPE0-S59최신 인증시험 덤프데모 <<

HPE0-S59최신 인증시험 덤프데모 100% 시험패스 덤프

DumpTOP는 자격증 응시자에게HP HPE0-S59 시험 준비를 위한 현재 그리고 가장 최근의 자료들을 제공하는 IT 산업 영역의 리더입니다. DumpTOP는HP HPE0-S59덤프를 시험문제변경에 따라 계속 갱신하여 고객님의게서 받은 것이 HP HPE0-S59 시험의 가장 최신 기출문제임을 보증해드립니다.

최신 HPE Technical HPE0-S59 무료샘플문제 (Q89-Q94):

질문 # 89

Your customer has an HPE Synergy platform deployed and managed using HPE OneView. The customer also has HPE Superdome Flex with RMC deployed. They plan to deploy a second nPar and HPE Superdome Flex 280. They plan to manage new components using HPE OneView. What must be done to achieve this goal?

- A. The customer has to add HPE Superdome Flex to the HPE OneView used to manage HPE Synergy
- B. The customer must use IL05 to add HPE Superdome Flex systems to HPE OneView
- **C. The customer must add a second Rack Management Controller for HPE Superdome Flex 280**
- D. The customer should deploy an HPE OneView appliance for HPE Superdome Flex management

정답: C

질문 # 90

You modified a logical interconnect group that is used to configure logical interconnects in five different logical enclosures. What will be the impact of that change?

- A. All physical interconnects from the affected logical interconnects must be rebooted to activate the new configuration
- **B. All logical interconnects configured using this logical Interconnect group will report inconsistency**
- C. All physical interconnects from affected logical interconnects will be placed in a maintenance mode
- D. All logical interconnects configured using this logical interconnect group will be automatically updated

정답: B

설명:

When a logical interconnect group (LIG) that is used to configure logical interconnects in multiple logical enclosures is modified, all logical interconnects configured using this LIG will report inconsistency. This is because the configuration of the logical interconnects will no longer match the new settings defined in the modified LIG, and the inconsistencies must be resolved to ensure the configurations are synchronized.

질문 # 91

Your customer plans to add four HPE Synergy frames to an existing management ring. All installed frames are equipped with two 2-port FLM modules, while new frames will be equipped with 4-port FLM modules. Which statement about mixing different FLM modules is true?

- A. A management ring with mixed FLM modules cannot have more than 12 frames
- **B. A management ring can contain mixed frame link module configurations**
- C. Mixing different FLM modules is allowed if all of them have the same firmware version
- D. Existing 2-port FLM modules must be replaced with 4-port FLM modules

정답: B

설명:

In HPE Synergy, a management ring can indeed contain mixed frame link module (FLM) configurations. This means you can have a mix of 2-port and 4-port FLM modules within the same management ring without needing to replace the existing 2-port modules. This flexibility allows for gradual upgrades and scalability within the management ring.

질문 # 92

An HPE Synergy customer needs to prevent a timeout and loss of communication during an external switch firmware upgrade. Click the parameter that the customer should configure within an uplink set to meet this requirement

정답:

설명:

질문 # 93

What is a restriction of using a RoCE network?

- A. it is not supported with HPE Virtual Connect SE 40 GD F8 Module for HPE Synergy.
- B. It does not support Private VLAN and Multicast VLAN.
- **C. It does not support smart link and private network features.**
- D. It is by default configured as an untagged network and cannot be a part of a network set.

정답: C

설명:

A restriction of using a RoCE (RDMA over Converged Ethernet) network is that it does not support smart link and private network features. These features are essential for certain network configurations and use cases, but they are not available in RoCE networks, which are designed for high-performance, low-latency communication.

질문 # 94

.....

- [illegible]

그 외, DumpTOP HPE0-S59 시험 문제집 일부가 지금은 무료입니다: https://drive.google.com/open?id=10HKFA8-kO0JGs1bW4SvcdDpLvX-JI3_x